

V2.0 10.07.18


# Technical Data -VST6110G

The Hi-bond 6 series is automotive approved and has been tested by the Underwriters Laboratory UL746C. It has excellent adhesion to automotive plastics and painted steel. Other applications include sign and construction industries, automotive aftercare.

## **Product description**

- Foamed Acrylic Tape
- Colour: Grey
- Soft, tacky and conformable
- Ideal for use in automotive; engineering, sign and display manufacturing

### Construction



Item	Unit		Spec.		Test method	
Total thickness	mm	in	1.1(±0.1)	0.043(±0.004)	-	
Density	kg/m³	lb/ft³	780	49	-	
180° Peel Strength	gf/25mm	lbf/in	3900	8.6	ASTM-D-3330 (Stainless steel, room temp)	
Tensile Strength (T-Block Test)	gf/cm <sup>2</sup>	lbf/in²	6000	85.34	ASTM-D-897 (Aluminium, room temp)	
Dynamic Shear (after 20min)	gf/cm <sup>2</sup>	lbf/in²	3500	49.78	ASTM D-1002 (Stainless steel, room temp)	
Dynamic Shear (after 24hrs)	gf/cm²	lbf/in²	6000	85.34	ASTM D-1002 (Stainless steel, room temp)	
Temperature Resistance (Short Term)	°C	°F	160	320	-	
Temperature Resistance (Long Term)	°C	°F	100	212	-	
Low Temp. Resistance	°C	°F	-40	-40	-	
UV Resistance	-	-	Good	-	-	

Applications: Automotive, Engineering, Sign and display

#### **Note**

Unless stated otherwise all values given are average. All of the tapes in our range should be thoroughly tested on the substrates in the particular application they are intended for. Hi-Bond Tapes Ltd. will not be responsible for product failure unless full testing has been completed. The customer has to decide on the tapes suitability for the intended application.



# High Performance Tapes and Adhesive Products

1 Crucible Road, Phoenix Parkway, Corby, Northamptonshire NN17 5TS Telephone: +44 (0)1536 260022 Fax: +44 (0)1536 260044 email: sales@hi-bondtapes.co.uk www.hi-bondtapes.com

Company Registration No. 3985595

