



## Technical Datasheet

# AS810 PVC Slow Recovering Foam Tape

### Product Description

- Colour: Black/White
- Density: 100-120Kgs/M<sup>3</sup>
- Width: 1000mm - 1400mm
- Thickness: 2,3,4,5,6,8,10,12,15,18,20mm
- Roll Length: 25M to 130M according to the thickness.

### Technical Data

Properties	Unit	Value	Test Method
Density	kgs/M <sup>3</sup>	100-125	-
Tensile Strength	kpa	>150	DIN 53571
Elongation at Break	%	>120	DIN 53571
Tear Strength	N/mm	>80	DIN 53515
Compression Set	%	>45	DIN 53572
Compression Deflection	kpa	0s 12-33 60s 4-16	ASTM 1667
Shore 00 Hardness	-	20-40	-
Water Absorption	%	>30	-
Compression Water Seal	-	>30%	U-Test
Flammability	mm/min	<100/>6mm	FMVSS302
Temperature Range	°C	-30/+60	-



## Technical Datasheet

# S-4210 MF Adhesive Double Sided Tape

### Product Description

The MF-adhesive is a modified polyacrylate and has good, all-round adhesive properties especially with reference to ageing and weathering properties. It has very good initial tack with very high peel adhesion to a wide variety of low surface energy substrates such as foams, PE, PP and EPDM. MF-adhesive is an ideal lamination adhesive for a wide variety of laminates.

### Product Structure

<b>Support</b>	Non-woven, 12 g/m <sup>2</sup>
<b>Interliner</b>	Release paper, yellow, 90 g/ m <sup>2</sup>
<b>Adhesive weight</b>	90 g/m <sup>2</sup>
<b>Total Thickness</b>	0,10mm

### Characteristics

<b>Temperature resistance</b> (according to the ATP test method AA-B-12-07)	-40°C to +90 °C
<b>Adhesive strength</b> (according to AFERA 5001)	min 21 N/25mm Contact time: 1h