



Technical Datasheet

AS820 PVC Fast Recovery Foam Tape

Product Description

- Colour: Black/White
- Density: 200Kgs/M³
- Width: 1000mm - 1400mm
- Thickness: 2,3,4,5,6,8mm
- Roll Length: 40M to 100M according to the thickness.

Technical Data

Properties	Unit	Value	Test Method
Density	kgs/M ³	200-220	-
Tensile Strength	kpa	>279	DIN 53571
Elongation at Break	%	>125	DIN 53571
Compression Set 50% 23°C C/72 Hours	%	>30	DIN 53572
Compression Deflection	kpa	0s 25-50 60s 10-35	ASTM 1667
Shore 00 Hardness	-	25-42	-
Water Absorption	%	<11	-
Compression Water Seal	-	>20%	-
Flammability	mm/min	<100/>4mm	FMVSS302
Temperature Range	°C	-30/+80	-



Technical Datasheet

S-4710 AR Adhesive Double Sided Tape

Product Description

The AR-Adhesive is a modified acrylic, which provides excellent adhesion properties that increase over time, the adhesive also exhibits superior humidity and climate resistance when applied. The AR adhesive also provides excellent adhesion properties onto a very wide variety of surfaces including low energy surfaces such as PE, PP & EPDM. The high temperature resistance of this adhesive is also highly advantageous in many applications. Also, the AR adhesive is APEO free.

Product Structure

Support	Without Carrier, transfer
Interliner	Release paper, yellow, 90g/m ²
Adhesive weight	100g/m ²
Total Thickness	0,10mm

Characteristics

Temperature resistance (in accordance with ATP trial regulation 07)	-40°C to +160 °C
Adhesive strength (according to AFERA 5001)	min 24 N/25mm Contact time: 1h