

according to Regulation (EC) No 1907/2006

Kisling - 3110 pressure can

Revision date: 08.07.2024 Product code: 3110D Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Kisling - 3110 pressure can

UFI: FU9S-2VFG-A00K-C5DJ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives and sealants

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Kisling AG

Street: Motorenstrasse 102
Place: CH-8620 Wetzikon
Telephone: +41 58 272 0 272

E-mail: customerservice@kisling.com

Contact person: Product Compliance Telephone: +49 7940 5096 143

E-mail: compliance@kisling.com
Internet: www.kisling.com

Supplier

Company name: Kisling (Deutschland) GmbH

Street: Salzstraße 15
Place: D-74676 Niedernhall
Telephone: +49 7940 50961 61

E-mail: customerservice@kisling.com

Contact person: Product Compliance Telephone: +49 7940 5096 143

E-mail: compliance@kisling.com

Internet: www.kisling.com

1.4. Emergency telephone 24 hr. emergency phone number +1 872 5888271 (KAR)

<u>number:</u> Medicines & Poisons Info Office +356 2545 6508

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 1; H222-H229

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H222 Extremely flammable aerosol.



according to Regulation (EC) No 1907/2006

Kisling - 3110 pressure can

Revision date: 08.07.2024 Product code: 3110D Page 2 of 13

H229 Pressurised container: May burst if heated.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

EUH208 Contains Dimethylbis[(1-oxoneodecyl)oxy]stannane. May produce an allergic reaction.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances listed below with nonhazardous components.

Relevant ingredients

CAS No	Chemical name	Chemical name			
	EC No	Index No	REACH No		
	Classification (Regulation (EC) No	1272/2008)			
37859-55-5	2-Pentanone, 2,2',2"-[O,O',O"-(met	hylsilylidyne)trioxime]		1 - < 5 %	
	484-460-1		01-2120004323-76		
	Acute Tox. 4, Eye Irrit. 2; H302 H3	1, Eye Irrit. 2; H302 H319			
58190-62-8	2-Pentanone, 2,2',2"-[O,O',O"-(ethenylsilylidyne)trioxime]			1 - < 5 %	
	700-810-0		01-2120006148-66		
	Acute Tox. 4, Eye Irrit. 2; H302 H319				
68928-76-7	Dimethylbis[(1-oxoneodecyl)oxy]sta	annane		< 0.1 %	
	273-028-6		01-2120770324-57		
	Repr. 2, Acute Tox. 4, Skin Irrit. 2, 8 H315 H317 H372 H412	Skin Sens. 1A, STOT RE 1, Aquatic	Chronic 3; H361d H302		

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. I	Specific Conc. Limits, M-factors and ATE		
37859-55-5	484-460-1	2-Pentanone, 2,2',2"-[O,O',O"-(methylsilylidyne)trioxime]	1 - < 5 %	
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = ca. 1234 mg/kg			
58190-62-8	700-810-0	2-Pentanone, 2,2',2"-[O,O',O"-(ethenylsilylidyne)trioxime]	1 - < 5 %	
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 1000 - < 2000 mg/kg			
68928-76-7	273-028-6	Dimethylbis[(1-oxoneodecyl)oxy]stannane	< 0.1 %	
	dermal: LD50 =	= >2000 mg/kg; oral: LD50 = 892 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.



Kisling AG

according to Regulation (EC) No 1907/2006

Kisling - 3110 pressure can

Revision date: 08.07.2024 Product code: 3110D Page 3 of 13

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary. In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink 1 glass of of water. Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Powder.

5.2. Special hazards arising from the substance or mixture

Reignition possible over considerable distance. Vapours can form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

Danger of serious damage to health by prolonged exposure.

Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers. Wear a self-contained breathing apparatus and chemical protective clothing. Move undamaged containers from immediate hazard area if it can be done safely. Evacuate area.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking. Ventilate affected area. Avoid breathing spray. See protective measures under point 7 and 8.

6.2. Environmental precautions

Avoid release to the environment. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Use non-sparking tools. Prevent spread over a wide area (e.g. by containment or oil barriers). Retain contaminated washing water and dispose it.

For cleaning up

Soak up inert absorbent and dispose as waste requiring special attention.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13





according to Regulation (EC) No 1907/2006

Kisling - 3110 pressure can

Revision date: 08.07.2024 Product code: 3110D Page 4 of 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Only use the material in places where open light, fire and other flammable sources can be kept away. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means

Advice on general occupational hygiene

Draw up and observe skin protection programme. Avoid contact with skin, eyes and clothes. Avoid breathing spray. When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place. Protect from sunlight.

Hints on joint storage

Do not store together with:

Pyrophoric or self-heating substances, Organic peroxides and self-reactive substances, Flammable solids, gas, Blasting agent

Further information on storage conditions

5 - 30°C

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
37859-55-5	2-Pentanone, 2,2',2"-[O,O',O"-(methylsilylidyne)trioxime]			
Worker DNEL,	long-term	inhalation	systemic	0,229 mg/m³
Worker DNEL,	long-term	dermal	systemic	0,065 mg/kg bw/day
Consumer DNI	EL, long-term	dermal	systemic	0,033 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	0,057 mg/m³
Consumer DNEL, long-term		oral	systemic	0,033 mg/kg bw/day
58190-62-8	2-Pentanone, 2,2',2"-[O,O',O"-(ethenylsilylidyne)trioxime]			
Worker DNEL,	long-term	inhalation	systemic	0,229 mg/m³
Worker DNEL, long-term		dermal	systemic	0,065 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,057 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,033 mg/kg bw/day
Consumer DNI	EL, long-term	oral	systemic	0,033 mg/kg bw/day



according to Regulation (EC) No 1907/2006

Kisling - 3110 pressure can

Revision date: 08.07.2024 Product code: 3110D Page 5 of 13

PNEC values

CAS No	Name of agent	
Environmenta	I compartment	Value
37859-55-5	2-Pentanone, 2,2',2"-[O,O',O"-(methylsilylidyne)trioxime]	
Freshwater		0,1 mg/l
Marine water		0,01 mg/l
Freshwater se	ediment	0,569 mg/kg
Marine sediment		0,057 mg/kg
Micro-organisms in sewage treatment plants (STP)		2,15 mg/l
Soil	Soil	
58190-62-8	2-Pentanone, 2,2',2"-[O,O',O"-(ethenylsilylidyne)trioxime]	
Freshwater		0,103 mg/l
Marine water		0,01 mg/l
Freshwater sediment		0,586 mg/kg
Marine sediment		0,059 mg/kg
Micro-organisms in sewage treatment plants (STP)		2,22 mg/l
Soil		0,046 mg/kg

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Suitable material:

Thickness of the glove material 0,45 mm

> 480 min

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Self-contained respirator (breathing apparatus)

Thermal hazards

Heating causes rise in pressure with risk of bursting.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Paste



according to Regulation (EC) No 1907/2006

Kisling - 3110 pressure can

Revision date: 08.07.2024 Product code: 3110D Page 6 of 13

Colour: black

Odour: characteristic
Odour threshold: not determined

Melting point/freezing point:

Boiling point or initial boiling point and

not determined

not applicable

boiling range:

Flammability: not applicable not determined Lower explosion limits: Upper explosion limits: not determined Flash point: not applicable not determined Auto-ignition temperature: not determined Decomposition temperature: pH-Value: not determined not determined Viscosity / kinematic: not determined Water solubility:

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Density (at 20 °C):

Relative density:

Relative vapour density:

Not determinable due to hydrolysis.

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Oxidizing properties

not determined

Other safety characteristics

Evaporation rate: not determined Solid content: not determined Viscosity / dynamic: not determined

(at 25 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Materials to avoid:

10.4. Conditions to avoid

Avoid high temperatures or direct sunlight.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.



according to Regulation (EC) No 1907/2006

Kisling - 3110 pressure can

Revision date: 08.07.2024 Product code: 3110D Page 7 of 13

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 19402 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
37859-55-5	2-Pentanone, 2,2',2"-	[O,O',O"-(meth	nylsilylidyne)tr	ioxime]			
	oral	LD50 mg/kg	ca. 1234	Rat	Study report (2008)	OECD Guideline 425	
	dermal	LD50 mg/kg	> 2000	Rat	Study report (1995)	EU Method B.3	
58190-62-8	2-Pentanone, 2,2',2"-[O,O',O"-(ethenylsilylidyne)trioxime]						
	oral	LD50 < 2000 m	> 1000 - g/kg	Rat	Study report (2012)	OECD Guideline 423	
	dermal	LD50 mg/kg	> 2000	Rat	Study report (1995)	EU Method B.3	
68928-76-7	Dimethylbis[(1-oxone	odecyl)oxy]sta	nnane				
	oral	LD50 mg/kg	892	Rat	Study report (2001)	OECD Guideline 401	
	dermal	LD50 mg/kg	>2000	Rat	Pre-supplier/manufac turer		

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains Dimethylbis[(1-oxoneodecyl)oxy]stannane. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available



according to Regulation (EC) No 1907/2006

Kisling - 3110 pressure can

Revision date: 08.07.2024 Product code: 3110D Page 8 of 13

Practical experience

No data available

11.2. Information on other hazards

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
37859-55-5	2-Pentanone, 2,2',2"-[O,O',O"-(methylsilylidyne)trioxime]						
	Acute fish toxicity	LC50 mg/l	> 113	96 h		REACh Registration Dossier	
	Acute algae toxicity	ErC50	100 mg/l	72 h		REACh Registration Dossier	
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	REACh Registration Dossier	OECD Guideline 202
58190-62-8	2-Pentanone, 2,2',2"-[O,O',O"-(ethenylsilylidyne)trioxime]						
	Acute fish toxicity	LC50 mg/l	> 117	96 h		REACh Registration Dossier	
	Acute algae toxicity	ErC50	103 mg/l	72 h		REACh Registration Dossier	
	Acute crustacea toxicity	EC50 mg/l	> 117	48 h		REACh Registration Dossier	
68928-76-7	Dimethylbis[(1-oxoneodecyl)oxy]stannane						
	Acute algae toxicity	ErC50	7,6 mg/l		Raphidocelis subcapitata	REACh Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50	39 mg/l	48 h	Daphnia magna	REACh Registration Dossier	OECD Guideline 202

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
37859-55-5	2-Pentanone, 2,2',2"-[O,O',O"-(methylsilylidyne)trioxime]	ca. 1,25
58190-62-8	2-Pentanone, 2,2',2"-[O,O',O"-(ethenylsilylidyne)trioxime]	ca. 1,25
68928-76-7	Dimethylbis[(1-oxoneodecyl)oxy]stannane	5,503



according to Regulation (EC) No 1907/2006

Kisling - 3110 pressure can

Revision date: 08.07.2024 Product code: 3110D Page 9 of 13

BCF

CAS No	Chemical name	BCF	Species	Source
37859-55-5	2-Pentanone, 2,2',2"-[O,O',O"- (methylsilylidyne)trioxime]	3,103		REACh Registration D
58190-62-8	2-Pentanone, 2,2',2"-[O,O',O"- (ethenylsilylidyne)trioxime]	3,103		REACh Registration D

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances;

hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded

chemicals; gases in pressure containers (including halons) containing hazardous substances;

hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal

packaging waste); metallic packaging

Contaminated packaging

Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es): 2

14.4. Packing group:

Hazard label: 2



Classification code:



according to Regulation (EC) No 1907/2006

Kisling - 3110 pressure canRevision date: 08.07.2024 Product code: 3110D Page 10 of 13

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: 63 190 277 327 344 381 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:

IATA-max. quantity - Passenger:

IATA-packing instructions - Cargo:

IATA-max. quantity - Cargo:

150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No





according to Regulation (EC) No 1907/2006

Kisling - 3110 pressure can

Revision date: 08.07.2024 Product code: 3110D Page 11 of 13

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 40, Entry 75

Directive 2010/75/EU on industrial

3.938 % (49.219 g/l)

emissions:

Information according to Directive

2012/18/EU (SEVESO III):

P3a FLAMMABLE AEROSOLS

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of

child-bearing age.

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information



according to Regulation (EC) No 1907/2006

Kisling - 3110 pressure can

Revision date: 08.07.2024 Product code: 3110D Page 12 of 13

Abbreviations and acronyms

Aerosol: Aerosol

Acute Tox: Acute toxicity Skin Irrit: Skin irritation Eye Irrit: Eye irritation Skin Sens: Skin sensitisation Repr: Reproductive toxicity

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules MFAG: Medical First Aid Guide

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data

Relevant H and EUH statements (number and full text)

H229 Pressurised container: May burst if heated.

H302 Harmful if swallowed.



according to Regulation (EC) No 1907/2006

Kisling - 3110 pressure can				
Revision date: 08.07.2024	Product code: 3110D	Page 13 of 13		
H315	Causes skin irritation.			
H317	May cause an allergic skin reaction.			
H319	Causes serious eye irritation.			
H361d	Suspected of damaging the unborn child.			
H372	Causes damage to organs through prolonged or repeated exposure.			
H412	Harmful to aquatic life with long lasting effects.			
EUH208	Contains Dimethylbis[(1-oxoneodecyl)oxy]stannane. May produce an allergic reaction.			

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)