



Printing date 12.04.2023 Version number 2 (replaces version 1) Revision: 12.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- -1.1 Product identifier
- Trade name: 4451
- -1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture Adhesives
- -1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Kisling AG

Motorenstrasse 102

CH-8620 Wetzikon

Tel: +41-58-272 0 272

- Further information obtainable from: Product safety department
- Department issuing MSDS: info@kisling.com
- 1.4 Emergency telephone number:

Tox Info Suisse: 145 / +41-44-2 51 51 51

+49-700-24 112 112 (KAR)

+1 872 5888271

SECTION 2: Hazards identification

- -2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

-2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms





GHS05

GHS07

- Signal word Danger

- Hazard-determining components of labelling:

methacrylic acid, monoester with propane-1,2-diol acrylic acid

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane

- Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements

P261 Avoid breathing vapours.

(Contd. on page 2)

Printing date 12.04.2023 Version number 2 (replaces version 1) Revision: 12.04.2023

Trade name: 4451

(Contd. of page 1)

P280 Wear protective gloves / eye protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

- -2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- -3.2 Mixtures
- Description: Adhesive

| - Description: Adhesive | | |
|--|---|--------------|
| - Dangerous components: | | |
| CAS: 27813-02-1 EINECS: 248-666-3 Index number: 607-125-00-5 | methacrylic acid, monoester with propane-1,2-diol Eye Irrit. 2, H319; Skin Sens. 1, H317 | > 15 - ≤ 30% |
| CAS: 79-10-7 EINECS: 201-177-9 Index number: 607-061-00-8 | acrylic acid Flam. Liq. 3, H226; Skin Corr. 1A, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332 Specific concentration limit: STOT SE 3; H335: C ≥ 1 % | ≥ 3 - < 5% |
| CAS: 80-15-9 EINECS: 201-254-7 Index number: 617-002-00-8 | α, $α$ -dimethylbenzyl hydroperoxide Org. Perox. E, H242; Acute Tox. 3, H331; STOT RE 2, H373; Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; STOT SE 3, H335 Specific concentration limits: Skin Corr. 1B; H314: C ≥ 10 % Skin Irrit. 2; H315: 3 % ≤ C < 10 % Eye Dam. 1; H318: C ≥ 3 % Eye Irrit. 2; H319: 1 % ≤ C < 3 % STOT SE 3; H335: C < 10 % | >1 -< 2.5% |
| CAS: 2530-83-8 EINECS: 219-784-2 | [3-(2,3-epoxypropoxy)propyl]trimethoxysilane Eye Dam. 1, H318; Aquatic Chronic 3, H412 | > 1 - < 2.5% |
| CAS: 114-83-0 EINECS: 204-055-3 | 2'-phenylacetohydrazide Acute Tox. 3, H301 | ≤ 1% |
| CAS: 123-31-9 EINECS: 204-617-8 Index number: 604-005-00-4 | 1,4-dihydroxybenzene Muta. 2, H341; Carc. 2, H351; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Acute Tox. 4, H302; Skin Sens. 1, H317 | < 0.025% |

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- -4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact:

After contact with skin, wash immediately with plenty of soap and water.

If skin irritation continues, consult a doctor.

(Contd. on page 3)

Printing date 12.04.2023 Version number 2 (replaces version 1) Revision: 12.04.2023

Trade name: 4451

(Contd. of page 2)

- After eye contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

- After swallowing:

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting: seek medical advice and show this container or label.

-4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

-4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

-5.1 Extinguishing media

- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

-5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

-5.3 Advice for firefighters

- Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

- Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

- 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

-6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 10 for information on "stability and reactivity".

See Section 13 for disposal information.

SECTION 7: Handling and storage

-7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

- Information about fire - and explosion protection:

No special precautions are necessary if used and stored according to specifications.

-7.2 Conditions for safe storage, including any incompatibilities

- Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Not required.

(Contd. on page 4)

Printing date 12.04.2023 Version number 2 (replaces version 1) Revision: 12.04.2023

Trade name: 4451

(Contd. of page 3)

- Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

- Storage class (TRGS 510, Storage of hazardous substances in non-stationary containers): 10-13
- -7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

1 mg/l

0.1 mg/l

PNEC Freshwater

PNEC Marinewater

-8.1 Control parameters

| | | ol parame | | |
|--------|-----------------------|-------------|------------|--|
| _ | | ts with lin | | s that require monitoring at the workplace: |
| | | • | | 1 50 / 3 20 |
| MAK | (SW | itzeriana) | | rm value: 59 mg/m³, 20 ppm rm value: 29 mg/m³, 10 ppm |
| | | | S SSc; | in value. 25 mg in , 10 ppm |
| 123-3 | 1-9 1 | ,4-dihydr | - | ene |
| | | | • | rm value: 2 e mg/m³ |
| | ` | ĺ | | rm value: 2 e mg/m³ |
| | | | H S C2 N | M2; |
| - DNEI | Ls | | | |
| 27813 | 3-02- | | • | , monoester with propane-1,2-diol |
| Derma | al | Longterm | System | 4.2 mg/kg bw/day (General population) |
| | | | | ooxy)propyl]trimethoxysilane |
| Derma | al | Acute, Sy | | 21 mg/kg bw (Worker) |
| | | Longterm | System | 21 mg/kg bw/day (Worker) |
| Inhala | ative | Acute, Sy | | 147 mg/m³ (Worker) |
| | | | - | 147 mg/m³ (Worker) |
| | | ,4-dihydr | • | |
| Derma | al | Longterm | - | 64 mg/kg bw/day (General population) |
| | | | | 128 mg/kg bw/day (Worker) |
| Inhala | itive | Longterm | | 0.5 mg/m³ (General population) |
| | | | | 1 mg/m³ (Worker) |
| | | Longterm | - | 1.74 mg/m³ (General population) |
| | | | | 7 mg/m³ (Worker) |
| - PNEC | Cs | | | |
| 27813 | 3-02- | 1 methaci | rylic acid | , monoester with propane-1,2-diol |
| Oral | PNE | C oral | | mg/kg Food (General population) |
|] | PNEC Freshwa | | iter | 0.904 mg/l (General population) |
| [] | PNEC Freshwat | | iter sed | 6.28 mg/kg (General population) |
| [] | PNEC Marinewater | | water | 0.904 mg/l (General population) |
|] | PNEC Soil PNEC STP | | | 0.727 mg/kg (General population) |
| [] | | | | 10 mg/l (General population) |
|] | PNEC Marinewater se | | water sed | 6.28 mg/kg (General population) |

(Contd. on page 5)

Printing date 12.04.2023 Version number 2 (replaces version 1) Revision: 12.04.2023

Trade name: 4451

| | | (Contd. of page 4) |
|------------------------|----------------------|--------------------|
| 123-31-9 1,4-dihydroxy | benzene | |
| PNEC Freshwater | 0.114 mg/l | |
| PNEC Freshwater | sed 0.00098 mg/kg | |
| PNEC Marinewate | r 0.0114 mg/l | |
| PNEC Soil | 0.000129 mg/kg | |
| PNEC STP | 0.71 mg/l | |
| PNEC Marinewate | r sed 0.000097 mg/kg | |

- Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

- Hand protection

Protective gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

Find below a list of appropriate protective gloves for chemical surrounding:

Permeation time / penetration time: = 480 minutes (DIN EN 374):

Nitril I, Nr. 0730, 0732, 0733, 0736, 0737, 0738, 0739 oder 0836

Viton, Nr. 0890

Butyl II, Nr. 0897

Butyl, Nr. 0898

Permeation time / penetration time: = 240 minutes (DIN EN 374):

Naturlatex I, Nr. 0395 oder 0403

Chloropren Nitril II, Nr. 0717

Chloropren, Nr. 0720, 0722, 0723, 0725 oder 0726

Nitril VI, Nr. 0754

of KCL company (e-mail: vertrieb@kcl.de).

The recommendation is based exclusively on the chemical compatibility and the test according to EN374 under laboratory conditions.

Requirements can vary according to the use. Therefore, please always take into account the glove supplier's recommendations.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Version number 2 (replaces version 1) Printing date 12.04.2023 Revision: 12.04.2023

Trade name: 4451

(Contd. of page 5)

Permeation time / penetration time: see above (material of gloves)

- Eye/face protection Tightly sealed goggles

SECTION 9: Physical and chemical properties

- General Information

- Colour: Green - Odour: Characteristic - Odour threshold: Not determined. - Melting point/freezing point: Undetermined.

- Boiling point or initial boiling point and boiling

Undetermined. range - Flammability Not applicable.

-Lower and upper explosion limit

Not determined. - Lower: Not determined. - Upper: > 100 °C - Flash point: - Decomposition temperature: Not determined. 4 - 5

- pH at 20 °C - Viscosity:

- Kinematic viscosity

Not determined.

2,000 mPas (Brookfield (3/20)) - Dynamic at 20 °C:

- Solubility

Not miscible or difficult to mix. - water:

Not determined. - Partition coefficient n-octanol/water (log value) Not determined. - Vapour pressure:

- Density and/or relative density

- Density at 20 °C: 1.1 g/cm³ Not determined. - Relative density - Vapour density Not determined.

-9.2 Other information

- Appearance:

Fluid - Form:

- Important information on protection of health and environment, and on safety.

- Ignition temperature: Product is not self-igniting.

- Explosive properties: Product does not present an explosion hazard.

- Change in condition - Softening point/range

- Oxidising properties Not determined. - Evaporation rate Not determined.

- Information with regard to physical hazard classes

Void - Explosives - Flammable gases Void - Aerosols Void - Oxidising gases Void - Gases under pressure Void - Flammable liquids Void - Flammable solids Void - Self-reactive substances and mixtures Void - Pyrophoric liquids Void - Pyrophoric solids Void - Self-heating substances and mixtures Void

(Contd. on page 7)

Printing date 12.04.2023 Version number 2 (replaces version 1) Revision: 12.04.2023

Trade name: 4451

| | | (Contd. of page 6) |
|--|----------|--------------------|
| - Substances and mixtures, which emit fl | lammable | |
| gases in contact with water | Void | |
| - Oxidising liquids | Void | |
| - Oxidising solids | Void | |
| - Organic peroxides | Void | |
| - Corrosive to metals | Void | |
| - Desensitised explosives | Void | |

SECTION 10: Stability and reactivity

- -10.1 Reactivity No further relevant information available.
- -10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Protect from heat and direct sunlight.

- -10.3 Possibility of hazardous reactions Reacts with metal-salts.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- -11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

| - LD/LC50 | - LD/LC50 values relevant for classification: | | | |
|------------|---|--|--|--|
| 80-15-9 α, | 80-15-9 α,α -dimethylbenzyl hydroperoxide | | | |
| Oral | LD50 | 382 mg/kg (Rat, male/female) | | |
| Dermal | LD50 | 500 mg/kg (Rat, male/female) | | |
| Inhalative | LC50/4 h | 1.37 mg/l (Rat, male/female) | | |
| 2530-83-8 | [3-(2,3-ep | oxypropoxy)propyl]trimethoxysilane | | |
| Oral | LD50 | 8,025 mg/kg (Rat, male/female) (OECD TG 401) | | |
| Dermal | LD50 | 4,250 mg/kg (Rabbit) (OECD TG 402) | | |
| 114-83-0 2 | 114-83-0 2'-phenylacetohydrazide | | | |
| Oral | LD50 | 270 mg/kg (Rat, male/female) | | |
| 123-31-9 1 | 123-31-9 1,4-dihydroxybenzene | | | |
| Oral | LD50 | 375 mg/kg (Rat, male/female) (OECD 401) | | |
| Dermal | LD50 | > 2,000 mg/kg (Rabbit) (OECD 402) | | |

- Skin corrosion/irritation

Causes skin irritation.

- Serious eye damage/irritation

Causes serious eye damage.

- Respiratory or skin sensitisation

May cause an allergic skin reaction.

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause respiratory irritation.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 8)

Printing date 12.04.2023 Version number 2 (replaces version 1) Revision: 12.04.2023

Trade name: 4451

(Contd. of page 7)

- Additional toxicological information:

No experimentally found toxicological data are available for this preparation.

-11.2 Information on other hazards

- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- -12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- Toxicity to fish:

123-31-9 1,4-dihydroxybenzene

LC50/96 h 0.638 mg/l (Oncorhynchus mykiss)

- -12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- -12.7 Other adverse effects No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or undiluted sewage system.

SECTION 13: Disposal considerations

- -13.1 Waste treatment methods
- Recommendation Disposal must be made according to official regulations.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

| SECTION 14: Transport informat | IVII | |
|---|-----------------|--|
| - 14.1 UN number or ID number - ADR, IMDG, IATA | Void | |
| - 14.2 UN proper shipping name - ADR, IMDG, IATA | Void | |
| - 14.3 Transport hazard class(es) | | |
| - ADR, ADN, IMDG, IATA | | |
| - Class | Void | |
| - 14.4 Packing group | | |
| - ADR, IMDG, IATA | Void | |
| - 14.5 Environmental hazards: | Not applicable. | |
| - 14.6 Special precautions for user | Not applicable. | |

(Contd. on page 9)

Printing date 12.04.2023 Version number 2 (replaces version 1) Revision: 12.04.2023

Trade name: 4451

(Contd. of page 8)

| - 14.7 Maritime transport in bulk according to IMO | age 8) |
|--|--------|
| | |
| instruments Not applicable. | |
| - UN "Model Regulation": Void | |

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations:
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

H226 Flammable liquid and vapour.

H242 Heating may cause a fire.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Org. Perox. E: Organic peroxides – Type E/F

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 3: Acute toxicity - Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

(Contd. on page 10)

Page 10/10

(Contd. of page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.04.2023 Version number 2 (replaces version 1) Revision: 12.04.2023

Trade name: 4451

Skin Sens. 1: Skin sensitisation – Category 1 Muta. 2: Germ cell mutagenicity – Category 2

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

-* Data compared to the previous version altered.