



Technical
DATA

Scapa 0485

Rubber Resin Adhesive Strip - Amber, 0.4; 1 & 2mm

DESCRIPTION

Scapa 0485 is a solvent free rubber resin based hot melt adhesive. Scapa 0485 is available in amber in a strip format supplied on an easily removable, extended, white paper liner.

APPLICATIONS

- Fixing of carpets, decorative edging and board and trims
- Fixing roof bars on commercial vehicles
- Fixing of edgings, sheeting, signs and tiles
- Joining of plastic sheeting
- Bonding of insulation to walls
- As a temporary 'Third Hand' fix
- Mounting lightweight trim
- Bonding lightweight insulation panels, kickplates etc
- Jointing of plastic sheeting, filter membranes, damp proof membranes etc

PRODUCT BENEFITS

- Versatile "instant stick" adhesive on a roll
- Pre-formed to a choice of sizes
- Well established product with long term proven success
- Forms a strong waterproof bond
- Solvent free, therefore no fumes
- No curing time required
- Excellent bond strength
- Non-hardening and permanently flexible
- Very aggressive pressure sensitive adhesive
- Clean, easy to use alternative to brush on adhesives

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Cohesion	0.6	N/mm ²	55270*
Service Temperature	0 - 40	°C	-
Softening Point (Ring and Ball)	85	°C	55272*
Specific Gravity	0.98	g/cm ³	55295*
Tack (Rolling Ball Method)	30	mm	55233*

Note:

* Scapa Internal Test Method.

Note: should not be used where good chemical or UV resistance is required.

STANDARD PRESENTATIONS

- Thickness : 0.4mm; 1.0mm; 2.0mm
- Roll Length: 30m (0.4mm); 20m (1mm); 10m (2mm)
- Roll Width: 12mm, 19mm, 25mm, 38mm, 50mm
- Core: 76mm plain
- Packaging: Bulk packed

Note:

Note: Information on stock items, non-standard sizes, and lead times is available on request

RECOMMENDATIONS

It is recommended that this product is applied at temperatures over 10°C.

To aid the cutting of 0485, it is advisable to dip blades or scissors into water immediately prior to use. The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Service life will vary with conditions of use and is affected by climatic environment, but should not be less than one year from date of manufacture, if stored in a moderate climate and good conditions.