

# Sika® PowerClean Aid

## Cleaning aid for glass surfaces and removal of contamination

Technical Product Data (typical values) \*Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

Base	Open pore, expanded melamine resin
Color	White
Density	9.5 kg/m <sup>3</sup> approx.
Application method	Can be used with liquid or foaming glass cleaners
Shelf Life	36 months

### Description

Sika® PowerClean Aid has been specifically developed to remove contamination that cannot be sufficiently removed using standard glass cleaners only. When used in combination with foaming or liquid glass cleaner, Sika® PowerClean Aid removes contamination on a microscopic level without visibly scratching or otherwise damaging the glass surface.

### Product Benefits

- Removes contamination that cannot be removed with standard cleaners
- Removes contamination without scratching surface
- Aids in removing label residue on glass parts

### Areas of Application

Sika® PowerClean Aid is designed for the removal of contamination encountered on AGR ceramic frits and glass.

Industry



## Method of Application

### Application

Use any non-antistatic glass cleaner to wet the surface and detect contamination. Use Sika® PowerClean Aid and start scrubbing the bonding area around the perimeter of the glass. Sika® PowerClean Aid is designed for a single use on each glass part. Once the part has been treated with Sika® PowerClean Aid the part can be wiped clean with paper towels and more glass cleaner if necessary. Surfaces must be allowed to dry completely before the next step in surface preparation (e.g. application of Sika® Aktivator PRO) is performed. This product is to be used by experienced professional technicians only.

### Limitations

- Compatibility with the current substrate is to be verified prior to the application.
- Before applying Sika® PowerClean Aid to sensitive surfaces (e.g. plastics, etc.) it is recommended to test Sika® PowerClean Aid on a small, possibly non-visible area of the base material.
- Before application of adhesive, the surface has to be pre-treated according to Sika's surface preparation recommendations.
- If this product is used for other applications outside of Aftermarket Auto Glass Replacement, trials must be carried out prior to use.

### NON-HAZARDOUS

Not a hazardous substance or mixture. This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

### HMIS

Health	1
Flammability	0
Reactivity	0
Personal Protection	X

### First Aid

Wash skin thoroughly after handling. Use personal protective equipment as required. **IF INHALED:** Move to fresh air. **IF ON SKIN:** Wash with plenty of soap and water. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **IF SWALLOWED:** rinse mouth. Do NOT induce vomiting. **If eye irritation persists:** Get medical advice/ attention. If skin irritation or rash occurs: Get medical advice/ attention. **IF exposed or concerned:** Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

### Further Information

For further information and advice regarding transportation, handling, storage and disposal of chemical products, users should refer to the actual Material Safety Data Sheets containing physical, ecological, toxicological and other safety related data. It is highly recommended to read the actual Material Safety Data Sheet before using the product.

- **KEEP CONTAINER TIGHTLY CLOSED**
- **KEEP OUT OF REACH OF CHILDREN**
- **NOT FOR INTERNAL CONSUMPTION**
- **FOR INDUSTRIAL USE ONLY.**
- **FOR PROFESSIONAL USE ONLY**

Copies of the following publications are available on our website [www.sikausa.com](http://www.sikausa.com):

- Material Safety Data Sheets
- Product Data Sheet

**In case of emergency call:**  
**Chemtrec: 800-424-9300**  
**International: 703-527-3887**

### Packaging Information

Other	24 pieces per carton
-------	----------------------

### Value Basis

All technical data stated on this Product Data Sheet are based on the results of laboratory tests only.

Actual measured data in the field may vary due to site specific conditions which are not known to Sika and beyond our control.

### Limited Material Warranty

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

### Legal Notes/Disclaimer

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or

Further information available at:  
[www.sikausa.com](http://www.sikausa.com)

Sika Corporation  
Industry Division  
30800 Stephenson Highway  
Madison Heights, MI 48071  
USA  
Tel. 248 577 0020  
Fax 248 577 0810



arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s).

Sika reserves the right to change the properties of its products without notice. Sale of Sika products are subject Sika's Terms and Conditions of Sale available at [sikausa.com](http://sikausa.com) or by calling 201-933-8800.

Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Product Data Sheet, product label and Safety Data Sheet which are available online at [sikausa.com](http://sikausa.com) or by calling Sika's Technical Service Department at 800-933-7452. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Product Data Sheet, product label and Safety Data Sheet prior to product use.

Further information available at:  
[www.sikausa.com](http://www.sikausa.com)

Sika Corporation  
Industry Division  
30800 Stephenson Highway  
Madison Heights, MI 48071  
USA  
Tel. 248 577 0020  
Fax 248 577 0810

